



New!

Door-Oil

The great eco-friendly finishing treatment from Osmo to protect and preserve all internal wooden doors and joinery!

- Osmo Door-Oil is easy to use and gives a professional touch to internal doors
- High quality and durable finish – microporous
- Natural oil/wax based
- Water-repellent and indelible
- Does not crack, flake, peel or blister



Highest coverage!
A little goes a long way.
Approx. 12 m² with 2 coats.

Product description:

Osmo Door-Oil is a special oil and wax combination, used as a clear treatment on wooden doors and general interior joinery. Osmo Door-Oil is made on a base of natural plant oils and waxes. The surface will be protected against common household substances such as wine, beer, fizzy drinks, coffee, tea, fruit juices, milk and water in accordance with DIN 68861-1A (German industrial norm).

Preparation: The wooden surface must be clean and dry (max. 20% moisture content). Clean or lightly sand old microporous stains. Remove old varnish (use Osmo Paint Remover or sand down). If necessary sand down the surface using fine sand-paper (grit P120-150), remove dust carefully.

Methods of application:

Osmo Door-Oil is a clear, simple to use treatment. Please do not thin. Shake well before use.

Apply thinly, following the grain of the wood, with a thick natural bristle paintbrush (Osmo Natural Bristle Brush for example), Osmo Microfibre Roller or with a lint free cloth.

Leave to dry overnight for at least 8-10 hours.

Allow for good ventilation.

Apply second coat as above.

Again, leave this coat to dry for at least 8-10 hours with good ventilation.

If using a lint free cloth, apply 3-4 thin coats.

Cleaning your tools: Use Osmo Brush Cleaner (benzene-free) or turpentine.

Care and maintenance:

Using Osmo Door-Oil protects the door or any internal joinery from common household spillages, which can simply be cleaned off with water (or Osmo Wash and Care) and then wiped dry.

To remove stubborn stains, use Osmo Liquid Wax Cleaner, that both cleans and regenerates the surface.

For occasional renovation, reapply Osmo Door-Oil thinly to a clean surface.

Ingredients:

Based on natural vegetable oils (sunflower-oil, thistle-oil, soyabean-oil) and waxes (carnauba wax and candelilla wax), paraffins, lead-free siccatives (drying agents) and water-repellent additives; disaromatized white spirit (benzene-free). This product fulfills EU-regulation (2004/42/EC) according to the VOC limit value of max. 400 g/l (cat. A/e (2010)).

Does not contain biocides or preservatives
Safe for humans, animals and plants when dry
Suitable for children's toys
EN 71.3, DIN 63 160

Coverage:

Osmo Door-Oil is also good value - a 1 litre tin will cover 12 m² with 2 coats and has a shelf life of 5 years or more if can is tightly closed.

For further information please contact:

Osmo UK

Unit 24 Anglo Business Park, Smeaton Close, Aylesbury, Bucks HP19 8UP
phone 01296/481220, fax 01296/424090; www.osmouk.com, info@osmouk.com